

PRODUCT DATA SHEET

RYE ALLFLEET 15W/40

1) DESCRIPTION. A versatile 15W/40 diesel and petrol engine oil manufactured using a highly refined base stock together with detergent/dispersant, anti-wear and anti-oxidant additives to produce a mixed fleet oil.

2) APPLICATION. Both naturally aspirated or turbo charged diesel engines, and naturally aspirated four stroke petrol engines.

3) ADVANTAGES. Increased engine protection gives greater reliability
Improved performance under all conditions.
Maintains maximum engine efficiency.

4) SPECIFICATION.

ACEA	E2/B3/A3 (98)
API.	CH-4/CG-4/CF-4/SJ
MILITARY	MIL-L-2104E. MIL-L-46152C.
M.A.N.	271.
MACK	EO-M
VOLVO	VDS.
Cummins	CES 20,071
ZF	TE-ML-07

Exceeds the obsolete Caterpillar Series 3.

5) QUALITIES. Fluid at very low temperatures for easy cold starting and rapid circulation. Maintains viscosity for high temperature motorway conditions and other arduous conditions.
Detergent dispersant properties ensure reliable circulation during normal servicing periods and minimises formulation of harmful deposits on pistons. Good sludge control. Anti wear agents are included for protection of highly loaded rubbing surfaces.

6) TYPICAL CHARACTERISTICS.

SAE	15W/40
Kinematic Viscosity @ 100°C mm ² /s	14.5
Pour Point °C	-22
TBN (mgKOH/gm)	11.8.