PRODUCT DATA SHEET

RYE SLIDEWAY 68 , 220

DESCRIPTION. Special Slideway oils, for use on heavily loaded machine toolways, ensuring smooth table action even at slow speeds

APPLICATION. Lubrication of machine toolways under low speed or high load conditions .High film strength makes these oils excellent for slideways where stick-slip causes chatter and where fine feed adjustments are necessary. Other working parts of machinery where improved lubricity and non-drip haracteristics are desirable. Exhibits superior extreme pressure characteristics as can be seen from the Timken and 4 ball wear tests

QUALITES. Modified co-efficient of friction eliminates 'stick-up' at low speeds. Extreme pressure and anti-wear additives virtually eliminate all scoring and wear risks.

Timken OK Load (lbs)	D.2782	50.

Anti corrosion at high Temperatures.

Coppper strip (3 Hrs @ 100^0C)	D130	1A.

Passes the ASTM D665B test for anti rust properties.

.

TYPICAL CHARACTERISTICS.

ISO grade	68	220
Relative Density @ $15.^0$C	0.8	0.90
Kinematic Viscosity @40^0C, mm ^{2}/s	61.2-74.8	198-242
Flash Point ^{0}C	>150^0C	>150^0C
Pour Point ^{0}C	-12	-12

December 2002