

## PRODUCT DATA SHEET

# TRAFFIC FILM REMOVER

1) **DESCRIPTION.** A heavy duty power washer additive. A non-caustic, phosphate free formulation for both hot and cold cleaners. Suitable for both vehicle and plant cleaning operations.

2) **APPLICATION.** Rye Traffic Film Remover is a highly efficient and economic cleaner for the removal of traffic films, silt and caked mud on vehicle bodies. Also for the removal of grass/mud and oil on lawnmowers, agricultural machinery etc.

3) **ADVANTAGES.**

1. Non Caustic.
2. Phosphate free.
3. Bio-degradable.
4. Leaves a shiny finish.
5. Economical.

### 4) **DIRECTIONS FOR USE.**

Consult cleaner manufacturers instructions before use.  
For most equipment and applications dilute the concentrate 1-10 parts with water prior to use in the hot water cleaner.

#### **General guide to final dilution rates at nozzle.**

Traffic film removal	1:60 -1:120.
Engine degreasing	1:30 - 1:60
Chassis cleaning	1:40 - 1:80

To obtain the best result. wet the vehicle with water, especially in the summer. Apply Rye Traffic Film remover solution from the bottom of the vehicle working upwards.

Thoroughly pressure rinse off with hot or cold water.

Always use the mildest conditions i.e. coolest temperature and lowest concentration of additive to achieve a satisfactory result. Particularly if the vehicle has been re-sprayed.

**NEVER ALLOW TO DRY ON THE PAINTWORK OR STAINING MAY OCCUR**

### 5) **TYPICAL CHARACTERISTICS.**

Appearance,	water thin straw coloured liquid.
Specific Gravity,	1.050-1.100
Ph	13.00